## NSN 5305-00-151-3249



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-151-3249 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.348 inches and 0.385 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 2330 **Screw Material Specification:** Sae assn standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf

**Specification Or Standard:** 

3 type and 3c style

**Departure From Cited Designator:** 

As modified by matl, min tensile strength and hardness rating

Shelf Life:

N/a

**Unit Of Measure:** 

## **NSN 5305-00-151-3249** Machine Screw - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A500d0