NSN 5305-00-151-3395

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-151-3395



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.298 inches and 0.453 inches Fastener Length: Between 1.344 inches and 1.406 inches **Head Style:** Round extended washer **Head Diameter:** Between 0.365 inches and 0.385 inches **Head Height:** Between 0.089 inches and 0.099 inches **Extended Washer Diameter:** Between 0.427 inches and 0.447 inches **Extended Washer Thickness:** Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5305-00-151-3395

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-a-8625 spec.

