NSN 5305-00-151-3511

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-3511 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.257 inches and 0.422 inches **Fastener Length:** Between 0.406 inches and 0.469 inches **Head Style:** Round extended washer **Head Diameter:** Between 0.427 inches and 0.447 inches **Head Height:** Between 0.096 inches and 0.106 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.028 inches and 0.033 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 62000 pounds per square inch **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-151-3511

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.