NSN 5305-00-151-5702

Thread Class:

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-5702

| ou . |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.875 inches |
| Fastener Length: |
| Between 1.984 inches and 2.031 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.262 inches and 0.270 inches |
| Head Height: |
| Between 0.159 inches and 0.164 inches |
| Locking Feature: |
| Pellet threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.164 inches |
| Width Across Flats: |
| Between 0.141 inches and 0.143 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 155000 pounds per square inch |
| Material: |
| Steel fastener |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Cadmium fastener and chromate fastener |
| Surface Treatment Specification: |
| Qq-p-416, type 2 class 2 federal specification single treatment response fastener |
| Thread Series Designator: |
| Unc |
| Specification Data: |

80205-nas1352 professional/industrial association standard

NSN 5305-00-151-5702

Socket Head Cap Screw - Page 2 of 2



6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0