

View Online at <https://aerobasegroup.com/nsn/5305-00-151-5795>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.495 inches and 0.562 inches

**Fastener Length:**

Between 0.531 inches and 0.562 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.155 inches and 0.167 inches

**Head Height:**

Between 0.053 inches and 0.062 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

W/s: aircraft, stratofortress b-52; family of medium tactical vehicles-medium; helicopter, mh-53e; helicopter, electronic countermeasures, eh-60a; helicopter, observation (ahip), oh-58d; aircraft, b-2 bomber (atb); helicopter, seahawk, h-60; helicopter, iroquois uh-1; helicopter, advance attack, ah-1w

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Screw Material:**

Steel

**Screw Material Specification:**

Qq-s-634 federal specification single material response or qq-s-637 federal specification single material response or 66 federal standard single material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 9c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0