

View Online at <https://aerobasegroup.com/nsn/5305-00-151-6136>

Fastener Length:

Between 0.350 inches and 0.410 inches

Head Style:

Hexagon

Head Height:

Between 0.096 inches and 0.110 inches

Width Between Flats:

Between 0.244 inches and 0.250 inches

Internal Drive Style:

Slot

End Application:

W/s: helicopter, uscg search and rescue, hh-60j; field artillery ammunition support vehicle (faagv) (m992); helicopter, carrier based asw, sh-60f; aircraft, prowler ea-6b; helicopter, advance attack, ah-1w; helicopter, search and rescue, hh-60h; recovery vehicle, full-tracked medium, w/e (m88a1); helicopter, mh-53e; aircraft, c-2a (reprocured); helicopter, seahawk, h-60

Features Provided:

Casehardened

Nonmachine Thread Style:

Gimlet point (type a, ab or ba)

Nonmachine Thread Diameter:

0.164 inches

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Specification Or Standard:

Ab type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0