

View Online at <https://aerobasegroup.com/nsn/5305-00-151-6136>

**Fastener Length:**

Between 0.350 inches and 0.410 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.096 inches and 0.110 inches

**Width Between Flats:**

Between 0.244 inches and 0.250 inches

**Internal Drive Style:**

Slot

**End Application:**

W/s: helicopter, uscg search and rescue, hh-60j; field artillery ammunition support vehicle (faagv) (m992); helicopter, carrier based asw, sh-60f; aircraft, prowler ea-6b; helicopter, advance attack, ah-1w; helicopter, search and rescue, hh-60h; recovery vehicle, full-tracked medium, w/e (m88a1); helicopter, mh-53e; aircraft, c-2a (reprocured); helicopter, seahawk, h-60

**Features Provided:**

Casehardened

**Nonmachine Thread Style:**

Gimlet point (type a, ab or ba)

**Nonmachine Thread Diameter:**

0.164 inches

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Specification Or Standard:**

Ab type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0