NSN 5305-00-151-6154

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-6154 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.245 inches and 0.255 inches **Fastener Length:** Between 0.745 inches and 0.755 inches **Head Style:** Knurled no. 2 **Head Diameter:** Between 0.495 inches and 0.505 inches **Head Height:** Between 0.244 inches and 0.255 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.370 inches and 0.380 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Nonstandard point no. 6 with a nom diameter of 0.112 in. Nom lg of 0.125 in. Angle of point 60 degrees Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-151-6154

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0