

View Online at <https://aerobasegroup.com/nsn/5305-00-151-6158>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.750 inches

**Fastener Length:**

Between 2.219 inches and 2.281 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.112 inches and 1.188 inches

**Internal Drive Style:**

Hexagon

**End Application:**

W/s: trailer, semi, tank, 5000 gal, bulk; catapult/arresting gear

**Thread Diameter:**

0.625 inches

**Width Across Flats:**

0.375 inches

**Thready Qty Per Inch (tpi):**

11

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 43.0 rockwell c

**Minimum Yield Strength:**

130000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 84.0 degrees

**Material:**

Steel

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unc

**Specification Or Standard:**

4 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0