NSN 5305-00-151-6172

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-6172 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.418 inches and 1.556 inches **Fastener Length:** Between 1.563 inches and 1.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.249 inches and 0.279 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 430 or steel comp 302 or steel comp 303 or steel comp 303se **Screw Material Specification:** Qq-s-763 federal specification 1st material response or mil-s-7720 military specification 2nd material response or qq-s-764 federal specification 3rd material response or qq-s-764 federal specification 4th material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization:

NSN 5305-00-151-6172

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.