

View Online at <https://aerobasegroup.com/nsn/5305-00-151-6172>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.418 inches and 1.556 inches

**Fastener Length:**

Between 1.563 inches and 1.625 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.249 inches and 0.279 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 430 or steel comp 302 or steel comp 303 or steel comp 303se

**Screw Material Specification:**

Qq-s-763 federal specification 1st material response or mil-s-7720 military specification 2nd material response or qq-s-764 federal specification 3rd material response or qq-s-764 federal specification 4th material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 2c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-7720 spec.