Externally Relieved Body Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-151-6199



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.343 inches and 0.407 inches Fastener Length: Between 0.890 inches and 0.922 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.088 inches and 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.515 inches and 0.547 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303f or steel comp 303 plus x or steel comp

303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

1

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator: Unc Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig: 100260