Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-151-6877

Thread Class:3aThread Direction:Right-handThread Length:0.438 inchesFastener Length:0.500 inchesHead Style:ButtonHead Diameter:Between 0.298 inches and 0.312 inchesHead Height:Between 0.077 inches and 0.087 inchesInternal Drive Style:PetagonThread Diameter:0.164 inchesWith Across Flats:0.094 inchesStores Rating:36.0 rockwell c and 40.0 rockwell cMaterial:SteelSurface Treatment:NickelSurface Treatment:NickelSurface Treatment Specification single treatment responseThread Stries Designator:UncShelf Life:NiaNiaSurface Treatment Specification single treatment responseThread Stries Designator:NiaMin-p-6859 spec.	
Thread Direction: Right-hand Thread Length: 0.438 inches Fastener Length: 0.500 inches Head Style: Button Head Diameter: Between 0.298 inches and 0.312 inches Head Height: Between 0.077 inches and 0.087 inches Head Height: Between 0.077 inches and 0.087 inches Head Pioper Hexagon Thread Diameter: 0.164 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel Surface Treatment: Nickel Surface Treatment: Nickel Mit-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: - Demilitarization: No Fig: A003b0 Mil-std (military Standard):	Thread Class:
Right-handChread Length:0.438 inchesFastener Length:0.500 inchesHead Style:ButtonHead Diameter:Between 0.298 inches and 0.312 inchesHead Height:Between 0.077 inches and 0.087 inchesInternal Drive Style:HexagonThread Diameter:0.144 inchesWith Across Flats:0.094 inchesThready Qty Per Inch (tpi):32Hardness Rating:30.10 cockwell c and 40.0 rockwell cMaterial:NickelStrefe Treatment:NickelStrefe Treatment:NickelStrefe Treatment:Mith-be859 military specification single treatment responseThread Series Designator:UncSheff Life:NiaNiaStrefe:NiaStories Designator:NiaMith JohnesStrefe:NiaStories Designator:NiaStories Designator:Stories Designator:NiaStories Designator:NiaStories Designator:NiaStories Designator:NiaStories Designator:NiaStories Designator:NiaStories Designator:Stories Designator:Stories Designator:Stories Designator:Stories Designator:Stories Designator:Stories Designator:Stories	3a
Tread Length:         0.438 inches         Fastener Length:         0.500 inches         Head Style:         Button         Head Diameter:         Between 0.298 inches and 0.312 inches         Head Height:         Between 0.298 inches and 0.087 inches         Internal Drive Style:         Head Diameter:         0.404 inches         Width Across Flats:         0.094 inches         Thready Qty Per Inch (tpi):         32         Harnal Drive Style:         Steel         Steel         Steel         Steel         Strafee Treatment:         Nickel         Steel         Steel         Strafee Treatment:         Nickel         Stefle:         Nickel         Stefle:         Nickel         Diff Life:         N/a         Unc         Stefl Life:         N/a         Diff Life:         N/a         Diff Life:         N/a         Life:         Na         Liff Conteasure:	Thread Direction:
0.438 inchesFastener Length:0.500 inchesHead Style:ButtonHead Diameter:Between 0.298 inches and 0.312 inchesHead Height:Between 0.077 inches and 0.087 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:0.094 inchesThready Qty Per Inch (tpi):32Hardness Rating:36.0 rockwell c and 40.0 rockwell cMaterial:NickelSurface Treatment:NickelMil-p-6859 military specification single treatment responseThread Series Designator:NickelStel Ifie:NickelSurface Treatment:NickelDiffe:NickelStel Ifie:NickelStel Ifie:Stel Ifie:Nickel Ifie:Nickel Ifie:N	Right-hand
Fastener Length:0.500 inchesHead Style:ButtonHead Diameter:Between 0.298 inches and 0.312 inchesHead Height:Between 0.077 inches and 0.087 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:0.094 inchesThready Qty Per Inch (tpi):32Hardness Rating:36.0 rockwell c and 40.0 rockwell cMaterial:SteelSurface Treatment Specification single treatment responseThread Series Designator:UncShelf Life:NaDiameter:NickelEuria Series Designator:Mil-p-6859 military specification single treatment responseThread Series Designator:NaShelf Life:NaShelf SeriesSteelSurface Treatment Specification single treatment responseThread Series Designator:Nil-p-6859 military specification single treatment responseThread Series Designator:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:Shelf Life: <td< td=""><td>Thread Length:</td></td<>	Thread Length:
0.500 inchesHead Style:ButtonHead Diameter:Between 0.298 inches and 0.312 inchesHead Height:Between 0.077 inches and 0.087 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:0.094 inchesThready Qty Per Inch (tpi):32Hardness Rating:36.0 rockwell c and 40.0 rockwell cMaterial:SteelSurface Treatment:NickelMil-p-6859 military specification single treatment responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:NoFig:A003b0Mil-std (military Standard):	0.438 inches
Head Style:         Button         Head Diameter:         Between 0.298 inches and 0.312 inches         Head Height:         Between 0.077 inches and 0.087 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.164 inches         With Across Flats:         0.094 inches         Thready Oty Per Inch (tpi):         32         Hardness Rating:         36.0 rockwell c and 40.0 rockwell c         Material:         Steel         Sufface Treatment:         Nickel         Mil-p-6859 military specification single treatment response         Thread Series Designator:         Unc         Shelf Life:         N/a         Guit of Measure:         T-         Pemilitarization:         No         Fig:         A003b0	Fastener Length:
Button Head Diameter: Between 0.298 inches and 0.312 inches Head Height: Between 0.077 inches and 0.087 inches Head Height: Between 0.077 inches and 0.087 inches Internal Drive Style: Hexagon Thread Diameter: O.164 inches Vidth Across Flats: O.094 inches O.094 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel Surface Treatment: Nickel Surface Treatment Specification single treatment response Thread Series Designator: Unc Shelf Life: Na Chemilitarization: No Fig: A003b0 Hi-st (military Standard):	0.500 inches
Head Diameter: Between 0.298 inches and 0.312 inches Head Height: Between 0.077 inches and 0.087 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Vidth Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel Steel Surface Treatment: Nickel Surface Treatment: Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: Na Unit Of Measure:  Pemilitarization: No Fig: A003b0	Head Style:
Between 0.298 inches and 0.312 inchesHead Height:Between 0.077 inches and 0.087 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:0.094 inchesThready Qty Per Inch (tpi):32Hardness Rating:36.0 rockwell c and 40.0 rockwell cMaterial:SteelSurface Treatment:NickelMil-p-6859 military specification single treatment responseThread Series Designator:UncShelf Life:N/aThi Of Measure:-NoFig:A003b0Mil-sct (military Standard):	Button
Head Height:         Between 0.077 inches and 0.087 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.164 inches         Width Across Flats:         0.094 inches         Thready Qty Per Inch (tpi):         32         Hardness Rating:         36.0 rockwell c and 40.0 rockwell c         Material:         Steel         Surface Treatment:         Nickel         Surface Treatment Specification:         Mil-p-6859 military specification single treatment response         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:            Pemilitarization:         No         Fig:         A003b0         Mil-std (military Standard):	Head Diameter:
Between 0.077 inches and 0.087 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.164 inches         Width Across Flats:         0.094 inches         Thready Qty Per Inch (tpi):         32         Hardness Rating:         36.0 rockwell c and 40.0 rockwell c         Material:         Steel         Surface Treatment:         Nickel         Gurface Treatment:         Nickel         Surface Treatment Specification single treatment response         Thread Series Designator:         Unc         Shelf Life:         N/a         Demilitarization:         r-         Action of Measure:         a.         Action of Measure:         Motopoo         Motopoo	Between 0.298 inches and 0.312 inches
Internal Drive Style: Hexagon Hexagon Thread Diameter: 0.164 inches Uidth Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel Surface Treatment: Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0 Mil-std (military Standard):	Head Height:
HexagonThread Diameter:0.164 inchesWidth Across Flats:0.094 inchesThready Qty Per Inch (tpi):32Hardness Rating:36.0 rockwell c and 40.0 rockwell cMaterial:SteelSurface Treatment:NickelSurface Treatment Specification single treatment responseThread Series Designator:UncShelf Life:N/aDint Of Measure:MiMiderian:SteelSterelSurface Treatment Specification single treatment responseThread Series Designator:UncShelf Life:N/aDint Of Measure:Maion Dinter Series Designator:MiMiShelf Life:AliesMaion Dinter SeriesMaion Dinter Seri	Between 0.077 inches and 0.087 inches
Thread Diameter:         0.164 inches         Width Across Flats:         0.094 inches         Thready Qty Per Inch (tpi):         32         Hardness Rating:         36.0 rockwell c and 40.0 rockwell c         Material:         Steel         Surface Treatment:         Nickel         Surface Treatment Specification:         Mil-p-6859 military specification single treatment response         Thread Series Designator:         Unc         Shelf Life:         N/a         Dint Of Measure:            Fig:         A003b0         Mil-std (military Standard):	Internal Drive Style:
0.164 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: 36.0 rockwell c and 40.0 rockwell c Material: 37. 38. 39. 30. 30. 30. 30. 30. 31. 31. 32. 32. 32. 32. 32. 32. 32. 32. 32. 32	Hexagon
Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: 36.0 rockwell c and 40.0 rockwell c Material: 36.0 rockwell c and 40.0 rockwell c Material: 36.0 rockwell c and 40.0 rockwell c Material: 32 Steel Steel Steel Surface Treatment: Nickel Surface Treatment Specification: Nil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Thread Diameter:
0.094 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: 36.0 rockwell c and 40.0 rockwell c Material: 35teel Steel Surface Treatment: Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Lint Of Measure: Demilitarization: No Fig: A003b0 Mil-std (military Standard):	0.164 inches
Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel Surface Treatment: Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Width Across Flats:
32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel Steel Surface Treatment: Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure:  Demilitarization: No Fig: A003b0 Mil-std (military Standard):	0.094 inches
Hardness Rating:         36.0 rockwell c and 40.0 rockwell c         Material:         Steel         Surface Treatment:         Nickel         Surface Treatment Specification:         Mil-p-6859 military specification single treatment response         Thread Series Designator:         Unc         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:         A003b0         Mil-std (military Standard):	Thready Qty Per Inch (tpi):
36.0 rockwell c and 40.0 rockwell c Material: Steel Surface Treatment: Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	32
Material:SteelSurface Treatment:NickelSurface Treatment Specification:Mil-p-6859 military specification single treatment responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:A003b0Mil-std (military Standard):	Hardness Rating:
Steel Surface Treatment: Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0 Mil-std (military Standard):	36.0 rockwell c and 40.0 rockwell c
Surface Treatment: Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Material:
Nickel Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Steel
Surface Treatment Specification: Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Surface Treatment:
Mil-p-6859 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Nickel
Thread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:A003b0Mil-std (military Standard):	
Unc Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	
Unit Of Measure:  Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Shelf Life:
 Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	N/a
Demilitarization: No Fiig: A003b0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A003b0 Mil-std (military Standard):	
Fiig: A003b0 Mil-std (military Standard):	Demilitarization:
A003b0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A003b0
Mil-p-6859 spec.	Mil-std (military Standard):
	Mil-p-6859 spec.