## NSN 5305-00-151-6886

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-6886 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.169 inches and 0.200 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Primary Washer Outside Diameter:** Between 0.220 inches and 0.230 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.014 inches Material: Steel fastener **Material Specification:** Aisi assn standard single material response primary washer **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-151-6886

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.