## NSN 5305-00-151-8658



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-151-8658 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.329 inches and 0.389 inches **Fastener Length:** Between 1.024 inches and 1.054 inches **Head Style:** Flat countersunk **Head Diameter:** 0.357 inches **Grip Diameter:** Between 0.2540 inches and 0.2550 inches

Internal Drive Style:

Slot

**End Application:** 

W/s: aircraft, prowler ea-6b

**Thread Diameter:** 

0.250 inches

**Grip Length:** 

Between 0.665 inches and 0.695 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

150000 pounds per square inch

**Hardness Rating:** 

33.0 rockwell c

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

**Special Features:** 

Color tan, surface of head

Material:

Steel comp 4037

**Material Specification:** 

Aisi assn standard single material response

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:** 

Unf

## NSN 5305-00-151-8658

Close Tolerance Screw - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0