NSN 5305-00-151-8712



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-151-8712 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 2.000 inches **Fastener Length:** 3.500 inches **Head Style:** Flat chamfer **Head Diameter:** 1.500 inches **Head Height:** 1.000 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 1.000 inches Width Across Flats: 0.750 inches Thready Qty Per Inch (tpi): 14 **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Test Data Document:** 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-151-8712

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.