## NSN 5305-00-151-9929

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-9929 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.634 inches and 0.764 inches **Fastener Length:** Between 0.985 inches and 1.015 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.872 inches and 0.937 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.312 inches and 0.315 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf **Specification Or Standard:** 4 type

Shelf Life: N/a

## NSN 5305-00-151-9929

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0