NSN 5305-00-151-9930

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-151-9930 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.325 inches and 0.392 inches **Fastener Length:** Between 1.710 inches and 1.757 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.573 inches and 0.635 inches **Grip Diameter:** Between 0.3108 inches and 0.3117 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel **Material Specification:** Sps-m-107, standard pressed steel co mfr ref single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

Ch.

Shelf Life:

N/a

NSN 5305-00-151-9930

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0