## NSN 5305-00-152-4949

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-152-4949 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 3.190 inches **Head Style:** Flat chamfer **Head Diameter:** 0.225 inches **Head Height:** 0.200 inches **First Diameter From Head:** Between 0.137 inches and 0.143 inches **Second Diameter From Head:** Between 0.086 inches and 0.092 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.000 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.810 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-152-4949

Externally Relieved Body Screw - Page 2 of 2



		• -						
ш	ın	ıt (	r 1t	ΝЛ	മാ	CI.	ire:	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.