NSN 5305-00-152-9370

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-152-9370

view Online at https://aerobasegroup.com/nsn/5305-00-152-9370
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.134 inches and 0.266 inches
Fastener Length:
Between 0.234 inches and 0.266 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Internal Drive Style:
Hexagon
End Application:
W/s: aircraft, phantom f-4
Thread Diameter:
0.250 inches
Width Across Flats:
0.187 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel
Material Specification:
Astm-a493 assn standard 6th material response or aisi xm-7 assn standard 6th material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Specification Or Standard:
6 type

6 type

NSN 5305-00-152-9370

Socket Head Cap Screw - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0