## NSN 5305-00-153-2782

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-153-2782 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 1.500 inches **Head Style:** Hexagon **Head Height:** 0.230 inches Width Between Flats: 0.500 inches **First Diameter From Head:** 0.312 inches **Second Diameter From Head:** 0.250 inches **Third Diameter From Head:** 0.312 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.812 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.874 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.000 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 2 federal specification single treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-00-153-2782

Externally Relieved Body Screw - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0