

View Online at <https://aerobasegroup.com/nsn/5305-00-153-6356>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.495 inches and 0.625 inches

Fastener Length:

Between 0.595 inches and 0.625 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.365 inches and 0.375 inches

Head Height:

Between 0.244 inches and 0.250 inches

Hole Diameter:

Between 0.044 inches and 0.050 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

Between 0.188 inches and 0.190 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Hole Configuration Style:

Round

Surface Finish:

125.0 microinches threads

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty2, cl3 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0