Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-153-9339

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.562 inches
Fastener Length:
Between 2.990 inches and 3.010 inches
Head Style:
Fillister
Head Diameter:
Between 0.396 inches and 0.416 inches
Head Height:
Between 0.178 inches and 0.198 inches
Hole Diameter:
0.062 inches
First Diameter From Head:
Between 0.180 inches and 0.200 inches
Second Diameter From Head:
0.250 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.050 inches and 0.070 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 2.428 inches and 2.448 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Hole Quantity:
1
Ноје Туре:
Drilled
Thready Qty Per Inch (tpi):
20
Hole Configuration Style:
Round
Externally Relieved Body Diameter Quantity:
Material:
Steel comp 8735 or steel comp 8740
Material Specification:
Ams 6320 assn standard 1st material response or ams 6322 assn standard 2nd material response

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0