NSN 5305-00-156-2359

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-156-2359 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.369 inches **Fastener Length:** Between 0.765 inches and 0.797 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.283 inches and 0.332 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8740 or steel comp 8630 **Screw Material Specification:** Mil-s-60049 military specification 1st material response or mils-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0

NSN 5305-00-156-2359

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-60049 spec.