NSN 5305-00-156-2409

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-156-2409 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.398 inches and 0.429 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.462 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 55000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 2330 **Screw Material Specification:** Sae assn standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 3c style

Departure From Cited Designator:

As modified by material, as modified by metallic hardness rating

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-156-2409

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0