

View Online at <https://aerobasegroup.com/nsn/5305-00-156-2686>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.750 inches and 0.844 inches

**Fastener Length:**

Between 0.844 inches and 0.875 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.292 inches and 0.313 inches

**Head Height:**

Between 0.123 inches and 0.130 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

35000 pounds per square inch

**Screw Material:**

Steel or steel comp 303 or steel comp 303se or steel comp 302

**Screw Material Specification:**

Aa-s-763 class iv assn standard 1st material response or mil-s-7720 comp fm military specification 2nd material response or mil-s-7720 comp fm military specification 3rd material response or mil-s-7720 comp g military specification 4th material response

**Screw Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 4s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-7720 spec.