## NSN 5305-00-156-2688

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-156-2688

2a
Thread Direction:
Right-hand
Thread Length:
Between 0.344 inches and 0.375 inches
Fastener Length:
Between 0.344 inches and 0.375 inches
Head Style:
Fillister
Head Diameter:
Between 0.292 inches and 0.313 inches
Head Height:
Between 0.123 inches and 0.130 inches
Hole Diameter:
0.047 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Screw Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316
Screw Material Specification:
66 federal standard all material responses
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unf
Specification Data:
88044-an501 government standard and 81348-ff-s-92 government specification
•
Specification Or Standard:

## NSN 5305-00-156-2688

Machine Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0