## NSN 5305-00-157-8108

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-157-8108 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 1.625 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches **First Diameter From Head:** Between 0.133 inches and 0.143 inches **Second Diameter From Head:** Between 0.092 inches and 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.219 inches and 0.281 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.344 inches and 1.406 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-157-8108

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0