NSN 5305-00-159-1460

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-159-1460 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.343 inches **Fastener Length:** Between 0.281 inches and 0.343 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.240 inches and 0.260 inches **Head Height:** Between 0.057 inches and 0.062 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 16 **Primary Washer Outside Diameter:** Between 0.245 inches and 0.255 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.031 inches Material: Copper alloy primary washer **Surface Treatment:** Nickel primary washer **Surface Treatment Specification:** Esf+5, fscm 24655 mfr ref single treatment response primary washer **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-159-1460

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0