NSN 5305-00-159-1582

Socket Head Cap Screw - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5305-00-159-1562
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.859 inches and 1.016 inches
Fastener Length:
Between 0.984 inches and 1.016 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Width Across Flats:
Between 0.312 inches and 0.316 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel comp xm-7 fastener
Material Specification:
Astm a493 assn standard all material responses fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unc
Specification Data:
80205-pag1352 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-00-159-1582

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0