

View Online at <https://aerobasegroup.com/nsn/5305-00-159-5559>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.251 inches and 1.375 inches

Fastener Length:

Between 1.313 inches and 1.375 inches

Head Style:

Pan

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.087 inches and 0.097 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: helicopter, sea knight h-46; aircraft, hornet f/a-18; m1a2 heavy assault bridge (hab) wolverine, 5420-01-430-4247; helicopter, carrier based asw, sh-60f; tank, abrams m-1; helicopter, search and rescue, hh-60h; helicopter, seahawk, h-60; m1a2 system enhancement prog 2350-01-328-5967 (eaa cmbt85sep); m1a2 abrams tank, 2750-01-328-5964 (eaa cnbt85pk3)

Thread Diameter:

0.138 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Copper alloy

Screw Material Specification:

Qq-w-321 federal specification single material response or qq-b-613 federal specification single material response or qq-b-626 federal specification single material response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0