## NSN 5305-00-161-0698

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-161-0698 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.750 inches **Fastener Length:** Between 2.562 inches and 2.750 inches **Head Style:** Hexagon **Head Height:** Between 0.455 inches and 0.483 inches Width Between Flats: Between 1.100 inches and 1.125 inches **Shank Unthreaded Hole Diameter:** 0.140 inches first hole **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 10 Min. Tensile Strength (psi): 120000 pounds per square inch **Hardness Rating:** 25.0 rockwell c and 34.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 2.531 inches first hole Surface Finish: 63.0 microinches threads Material: Steel **Material Specification:** Sae gr 5 assn standard single material response **Surface Treatment:** 

Cadmium and chromate

#### **Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

#### **Thread Series Designator:**

Unc

#### **Specification Or Standard:**

2 type or 10p style or 5 grade

### Shelf Life:

N/a

# NSN 5305-00-161-0698

Hexagon Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0