## NSN 5305-00-162-2978

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-162-2978

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.455 inches and 0.505 inches
Fastener Length:
Between 0.648 inches and 0.688 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.385 inches
Head Height:
Between 0.125 inches and 0.140 inches
Shoulder Diameter:
0.245 inches and 0.255 inches first shoulder
Shoulder Length:
0.183 inches and 0.193 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Hardness Rating:
52.0 rockwell c
Shoulder Shape:
Round first shoulder
Product Name:
Navy special project
Material:
Steel
Material Specification:
Mil-s-46850, type 2 military specification single material response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5305-00-162-2978

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-46850 spec.