NSN 5305-00-162-2979

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-162-2979

Thread Class:

2a

Thread Direction:

2a **Thread Direction:** Right-hand Thread Length: Between 0.455 inches and 0.505 inches **Fastener Length:** Between 0.648 inches and 0.688 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.385 inches **Head Height:** Between 0.125 inches and 0.140 inches **Shoulder Diameter:** 0.245 inches first shoulder and 0.255 inches first shoulder **Shoulder Length:** 0.183 inches first shoulder and 0.193 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 52.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** Mil-s-46850 type 3 military specification single material response **Thread Series Designator:** Unf Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

NSN 5305-00-162-2979

Shoulder Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-46850 spec.