## NSN 5305-00-162-4531

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-162-4531 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.169 inches and 0.209 inches **Fastener Length:** Between 0.942 inches and 0.952 inches **Head Style:** Pan **Head Diameter:** Between 0.270 inches and 0.290 inches **Head Height:** Between 0.100 inches and 0.110 inches **Shoulder Diameter:** 0.186 inches first shoulder and 0.188 inches first shoulder **Shoulder Length:** 0.722 inches first shoulder and 0.732 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Demilitarization:** No

**Unit Of Measure:** 

## **NSN 5305-00-162-4531** Shoulder Screw - Page 2 of 2



Fiig:

A003b0