

View Online at <https://aerobasegroup.com/nsn/5305-00-162-4588>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.268 inches and 0.313 inches

**Fastener Length:**

Between 1.190 inches and 1.204 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.360 inches and 0.374 inches

**Head Height:**

Between 0.095 inches and 0.110 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1894 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.812 inches and 0.828 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

39.0 rockwell c and 45.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.095 inches first hole and 1.115 inches first hole

**Surface Finish:**

63.0 microinches grip

**Special Features:**

Plunger operated spring loaded retaining balls

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-416 type 2cl 3 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0