## NSN 5305-00-162-4588

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-162-4588 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.268 inches and 0.313 inches **Fastener Length:** Between 1.190 inches and 1.204 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.095 inches and 0.110 inches **Grip Diameter:** Between 0.1885 inches and 0.1894 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole and 0.080 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.812 inches and 0.828 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 1.095 inches first hole and 1.115 inches first hole **Surface Finish:** 63.0 microinches grip **Special Features:** Plunger operated spring loaded retaining balls **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-416 type 2cl 3 federal specification single treatment response fastener **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5305-00-162-4588

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0