

View Online at <https://aerobasegroup.com/nsn/5305-00-162-4816>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.250 inches and 0.317 inches

Fastener Length:

Between 1.198 inches and 1.245 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.377 inches and 0.385 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

Between 0.928 inches and 0.948 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Countersink Angle:

100.0 degrees

Surface Finish:

32.0 microinches grip

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-8844 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Tin

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-8844 spec.