## NSN 5305-00-163-2692

**Thread Class:** 

Right-hand

**Thread Direction:** 

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-163-2692

| Thread Length:                                  |
|---|
| Between 0.522 inches and 0.572 inches           |
| Fastener Length:                                |
| Between 1.157 inches and 1.187 inches           |
| Head Style:                                     |
| Flat countersunk                                |
| Head Diameter:                                  |
| Between 0.575 inches and 0.635 inches           |
| Grip Diameter:                                  |
| Between 0.3110 inches and 0.3120 inches         |
| Internal Drive Style:                           |
| Offset cruciform (torque set)                   |
| Thread Diameter:                                |
| 0.312 inches                                    |
| Grip Length:                                    |
| Between 0.615 inches and 0.635 inches           |
| Thready Qty Per Inch (tpi):                     |
| 24  |
| Min. Tensile Strength (psi):                    |
| 220000 pounds per square inch                   |
| Hardness Rating:                                |
| 46.0 rockwell c and 50.0 rockwell c             |
| Countersink Angle:                              |
| Between 99.0 degrees and 101.0 degrees          |
| Surface Finish:                                 |
| 32.0 microinches threads                        |
| Material:                                       |
| Steel comp h11                                  |
| Material Specification:                         |
| Ams 6487 assn standard single material response |
| Surface Treatment:                              |
| Nickel and cadmium                              |
| Surface Treatment Specification:                |
| Ams 2416 assn standard all treatment responses  |
| Thread Series Designator:                       |
| Unjf  |
| Shelf Life:                                     |
| N/a   |
|   |

## NSN 5305-00-163-2692

Close Tolerance Screw - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A003b0