NSN 5305-00-163-4739

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-163-4739

View Online at https://aerobasegroup.com/nsn/5305-00-163-4739
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.192 inches and 0.266 inches
Fastener Length:
Between 0.234 inches and 0.266 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.154 inches and 0.161 inches
Head Height:
Between 0.095 inches and 0.099 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.099 inches
Width Across Flats:
Between 0.078 inches and 0.079 inches
Thready Qty Per Inch (tpi):
48
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a

N/a

NSN 5305-00-163-4739

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0