NSN 5305-00-163-7558



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-163-7558 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.400 inches **Fastener Length:** Between 4.820 inches and 4.860 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.120 inches Width Between Flats: 0.312 inches **Shoulder Diameter:** 0.270 inches first shoulder and 0.290 inches first shoulder **Shoulder Length:** 4.280 inches first shoulder and 4.320 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.061 inches first hole and 0.065 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Distance From Head Largest Bearing Surface To Shank Hole Center: 0.530 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm 1582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

Unf

Shelf Life:

N/a

NSN 5305-00-163-7558

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0