NSN 5305-00-164-7377

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-164-7377 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.170 inches and 0.250 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Color: Black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Data:**

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-00-164-7377

Socket Head Cap Screw - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.