NSN 5305-00-165-1812

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-165-1812 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.252 inches and 0.355 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.480 inches and 0.531 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.156 inches and 0.158 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 70000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Qq-p-35 federal specification single treatment response

Steel comp 303 or steel comp 304 **Surface Treatment: Passivate Surface Treatment Specification: Thread Series Designator:** Unf **Specification Or Standard:** 4 type Shelf Life: N/a **Unit Of Measure:**

NSN 5305-00-165-1812

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0