NSN 5305-00-165-1812

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-165-1812



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.252 inches and 0.355 inches
Fastener Length:
Between 0.484 inches and 0.516 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.480 inches and 0.531 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.156 inches and 0.158 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
70000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Countersink Angle:
Between 80.0 degrees and 84.0 degrees
Material:
Steel comp 303 or steel comp 304
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Specification Or Standard:
4 type
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-00-165-1812

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

