NSN 5305-00-165-1820

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-165-1820 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 1.250 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.500 inches **Head Height:** 0.562 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Nonstandard point no. 6, 0.188 in. Lg, point angle 90.0 degrees, 0.175 in. dia. Of point Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-165-1820

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0