

View Online at <https://aerobasegroup.com/nsn/5305-00-165-5359>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.377 inches and 0.516 inches

**Fastener Length:**

Between 0.704 inches and 0.751 inches

**Head Style:**

Round

**Head Diameter:**

Between 0.361 inches and 0.385 inches

**Head Height:**

Between 0.103 inches and 0.118 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

W/s: aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, c-18a, ec-18b; aircraft, t-2; helicopter, seahawk h-60; submarine armament and fire control systems; f4s aircraft; missile, all-weather anti-ship, harpoon (agm-84); consolidated targets; support equipment, b-52 aircraft; joint stars target radar system.

**Thread Diameter:**

0.190 inches

**Thread Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

Between 26.0 rockwell c and 32.0 rockwell c

**Screw Material:**

Steel comp 8630

**Screw Material Specification:**

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6050 spec.