## NSN 5305-00-165-8033

Shoulder Screw - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5305-00-165-8033

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.490 inches and 0.510 inches
Fastener Length:
Between 2.047 inches and 2.077 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.542 inches and 0.562 inches
Head Height:
Between 0.244 inches and 0.250 inches
Shoulder Length:
1.229 inches first shoulder and 1.239 inches first shoulder
Shank Unthreaded Hole Diameter:
0.065 inches first hole and 0.072 inches first hole
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.188 inches and 0.190 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
40.0 rockwell c and 45.0 rockwell c
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.557 inches first hole and 1.567 inches first hole
Shoulder Shape:
Round first shoulder
Material:
Steel
Material Specification:
Astm a582 assn standard single material response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-00-165-8033

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

