

View Online at <https://aerobasegroup.com/nsn/5305-00-165-8074>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.443 inches

**Fastener Length:**

Between 2.906 inches and 3.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.302 inches and 0.323 inches

**Width Between Flats:**

Between 0.736 inches and 0.750 inches

**Hole Diameter:**

0.096 inches

**End Application:**

W/s: shipboard material handling equipment (mhe); fire pumps; aircraft, c-2a (reprocured); steam (std. Tensioned replenishment at sea method) main feed pumps; helicopter, mh-53e; missile, air intercept, sidewinder (aim-9); helicopter, advance attack, ah-1w; torpedo, mk 48

**Thread Diameter:**

0.500 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

13

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

25.0 rockwell c and 34.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel

**Material Specification:**

Sae gr 5 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style and 5 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0