

View Online at <https://aerobasegroup.com/nsn/5305-00-166-2110>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.488 inches

**Fastener Length:**

2.188 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 1.182 inches and 1.192 inches

**Head Height:**

Between 0.302 inches and 0.322 inches

**Shank Unthreaded Hole Diameter:**

2.047 inches first hole

**First Diameter From Head:**

Between 0.535 inches and 0.545 inches

**Second Diameter From Head:**

Between 0.686 inches and 0.687 inches

**Third Diameter From Head:**

Between 0.535 inches and 0.545 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.800 inches and 0.830 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 1.300 inches and 1.330 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 1.670 inches and 1.700 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.128 inches all holes

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Tin

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0