Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-168-2979

| Thread Class: |
|---|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.125 inches |
| Fastener Length: |
| Between 1.234 inches and 1.281 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.457 inches and 0.469 inches |
| Head Height: |
| Between 0.306 inches and 0.312 inches |
| Locking Feature: |
| Pellet threads or strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.312 inches |
| Width Across Flats: |
| Between 0.250 inches and 0.253 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 130000 pounds per square inch |
| Material: |
| Steel |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2 class 3 federal specification all treatment responses |
| Thread Series Designator: |
| Unc |
| Specification Data: |
| 80205-nas1352 professional/industrial association standard |
| 80205-nas1352 professional/industrial association standard |

NSN 5305-00-168-2979

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

